

# Windsor Plywood

## NATUR CORK

### FLOORING TIP GUIDE



QUICKSTYLE

#### PRE-INSTALLATION NOTES

- Store the material flat in the unopened packages for 48 hours at room temperature 64°F (18°C) prior to installation.
- Before installing the material, inspect all panels for flaws.
- Natur Cork flooring is laid floating, i.e. only the tongue and grooves are interlocked, both lengthwise and crosswise.
- Integrated cork backing, the use of any underlay, ex. (foam) is not required on the subfloor.

#### FEATURES & BENEFITS

- Thermal and acoustic properties
- Natural product
- Residential or commercial application
- 100% pure CORK top and bottom layer

#### PRE-VARNISHED CORK MODELS

- Under normal usage, no additional finishing is required for Natur Cork flooring.
- But in the case it is deemed necessary to further protect the seems against water infiltration or humidity, Another coat of varnish may be applied to the flooring 48 hours following the installation.
- Use a high quality hardwood flooring water-based or oil-based polyurethane varnish.

#### IMPORTANT TIP!

- It is recommended that the flooring be cleaned using a floor cleaning solution

#### TECHNICAL DATA

Panel Size	35 11/16" x 11 13/16" x 7/16"
Panels per box	6 Panels
Coverage per box	17.44 Square feet

CLEARANCE CENTER ONLY

EDMONTON - CLAREVIEW • 5255 - 128th AVE. • TEL: 478-9663 • FAX: 478-9064

TOLL FREE: 1-888-898-4999 • [www.windsor-edmonton.com](http://www.windsor-edmonton.com) Click to our website for great savings on 100's of items & loads of information

The *experts* you need to know!

Windsor Plywood